

**TECHNICAL PLASTIC AND METAL PARTS** 

						Sc	rew 11:	rivet 3	
Code	Description	Price euro/1000	% Price Change 1 2	Package A	АВС	D	Е	F	gr
113 0003 699 02	MP 113-03 NERO	292,00	+ 60% -	250 8	3 10	20	14	1.5	

Colour	Colour num					
black	699 (XXX	99 (XXX XXXX <b>XXX</b> XX)				
Colour description black Matches brillant Featured colours reserved. Due to the		easonably matches RAL colour9005 es in colour may occur.	;			
Material		Material nr				
Nylon - 66 PA - 66		02 (XXX XXXX XXX <b>XX</b> )				
A strong, tough and durable material. selflubricant properties ideal for slide strongst. Therefore always has to acc Nylon is self extinguishing. <b>Features</b>	bearings. Takes in	approx 2 % moisture (a little less the	an nylon-6) and is then at its			
feature	DIN	Resistance to	Valutation			
Relative density gr/cm <sup>3</sup>		Petrol				
Tensile strength MN/m <sup>2</sup>	1,14 60	Benzene	A			
Elongation at break %	140	Mineral oils	A			
Tensile modulus MN/m <sup>2</sup>	140	Vegetable oils	A			
Notched impact strength kJ/m <sup>2</sup>	17	Weak alkalis	A			
Ball indentation MN/m <sup>2</sup>	100	Strong alkalis	В			
Application temperature max °C	120	Weak acids	В			
Volume resistivity cm	10^15	Strong acids	С			
Dissapation factor tan. 10 <sup>3</sup> Hz	0,15	A = good				
Dielectric strength MV/m	30	<b>B</b> = doubtful				
Flammability UL94 > 1,6 mm	V2	<b>C</b> = poor				
······································						
Coefficient of friction (on steel)	0,3					

Technical informations are indicative and can be updated. Copyright Gandini Fasteners S.r.I. All rights reserved. No part of this web site may be reproduced in any form without express permission.

GANDINI FASTENERS SRL viale Pier Paolo Pasolini, 83 - 20099 Sesto S.Giovanni Milano Italy Tel. +39 02 241 047 250 Fax +39 02 241 047 74

Production and distribution of fasteners, fixing elements and mechanical parts machining

**GANDINI FASTENERS SRL** Sesto San Giovanni Mi - Italy **Sales department** 250@gandini.it tel +39 02 241 047 250

Administration 350@gandini.it tel +39 02 241 047 350