

TECHNICAL PLASTIC AND METAL PARTS

									Screw 11		
Co	de	Description	Price euro/1000	% Price C 1	Change 2	Package	АВС	D	Е	Fο	gr
113 1070	599 02	MP 113-10-70	237,00	+ 60%	-	250	739	17.5	12.1	1.4	

Colour								
black 599 (XXX XXX XXX XXX)								
Colour description black								
		onably matches RAL colour 9005						
Featured colours reserved. Due to the	e screen, difference	es in colour may occur.						
Material		Material nr						
Nylon - 66 PA - 66		02 (XXX XXXX XXX XX)						
General informations: A strong, tough and durable material. selflubricant properties ideal for slide	bearings. Takes in	approx 2 % moisture (a little less the	an nylon-6) and is then at its					
strongst. Therefore always has to acc Nylon is self extinguishing.	limatize for a few d	ays after injection moulding. Operat	tional temperature up to 120°C.					
Features		Chimical resistance						
feature	DIN	Resistance to	Valutation					
Relative density gr/cm ³	1,14	Petrol	А					
Tensile strength MN/m ²	60	Benzene	A					
Elongation at break %	140	Mineral oils	А					
Tensile modulus MN/m ²	1500	Vegetable oils	А					
Notched impact strength kJ/m ²	17	Weak alkalis	А					
Ball indentation MN/m ²	100	Strong alkalis	В					
	100	Weak acids	В					
	120	Trout doldo						
Application temperature max °C	120 10^15	Strong acids	С					
Application temperature max °C Volume resistivity cm	.=•		C					
Application temperature max °C Volume resistivity cm Dissapation factor tan. 10 ³ Hz Dielectric strength MV/m	10^15	Strong acids A = good B = doubtful	C					
Application temperature max °C Volume resistivity cm Dissapation factor tan. 10 ³ Hz Dielectric strength MV/m	10^15 0,15	Strong acids A = good	C					
Application temperature max °C Volume resistivity cm Dissapation factor tan. 10 ³ Hz	10^15 0,15 30	Strong acids A = good B = doubtful	C					

Technical informations are indicative and can be updated. Copyright Gandini Fasteners S.r.I. All rights reserved. No part of this web site may be reproduced in any form without express permission.

GANDINI FASTENERS SRL viale Pier Paolo Pasolini, 83 - 20099 Sesto S.Giovanni Milano Italy Tel. +39 02 241 047 250 Fax +39 02 241 047 74

Production and distribution of fasteners, fixing elements and mechanical parts machining

GANDINI FASTENERS SRL Sesto San Giovanni Mi - Italy **Sales department** 250@gandini.it tel +39 02 241 047 250

Administration 350@gandini.it tel +39 02 241 047 350