

TECHNICAL PLASTIC AND METAL PARTS

										ole g 159-		I
Code	Description	Price euro/1000	% Price 0	Change	Package	A	В	С	D	E	F	ar
159 7032 699 02	MP 159- 7-32	4.336,00	1 + 60%	2	10	M32	14.7			33		9.

Colour	Colour num	ber						
ack 699 (XXX XXX XXX XXX)								
Colour descriptionblackMatchesbrillantFeatured colours reserved. Due to the		easonably matches RAL colour9005 es in colour may occur.	5					
Material		Material nr						
Nylon - 66 PA - 66		02 (XXX XXXX XXX XX)						
General informations: A strong, tough and durable material. selflubricant properties ideal for slide to strongst. Therefore always has to accl Nylon is self extinguishing.	pearings. Takes in	approx 2 % moisture (a little less th	an nylon-6) and is then at its					
Features		Chimical resistance						
feature	DIN Resistance to		Valutation					
Relative density gr/cm ³	1,14	Petrol	А					
Tensile strength MN/m ²	60	Benzene	А					
Elongation at break %	140	Mineral oils	А					
Tensile modulus MN/m ²	1500	Vegetable oils	А					
Notched impact strength kJ/m ²	17	Weak alkalis	А					
Ball indentation MN/m ²	100	Strong alkalis	В					
Application temperature max °C	120	Weak acids	В					
Volume resistivity cm	10^15	Strong acids	С					
Dissapation factor tan. 10 ³ Hz	0,15	A = good						
Dielectric strength MV/m	30	B = doubtful						
Flammability UL94 > 1,6 mm	V2	C = poor						
Coefficient of friction (on steel)	0,3							
All data are indicative								

Technical informations are indicative and can be updated. Copyright Gandini Fasteners S.r.I. All rights reserved. No part of this web site may be reproduced in any form without express permission.

GANDINI FASTENERS SRL viale Pier Paolo Pasolini, 83 - 20099 Sesto S.Giovanni Milano Italy Tel. +39 02 241 047 250 Fax +39 02 241 047 74

Production and distribution of fasteners, fixing elements and mechanical parts machining

GANDINI FASTENERS SRL Sesto San Giovanni Mi - Italy **Sales department** 250@gandini.it tel +39 02 241 047 250

Administration 350@gandini.it tel +39 02 241 047 350