

**TECHNICAL PLASTIC AND METAL PARTS** 

							kut riv <b>093</b>	/et
Code	Description	Price euro/1000	% Price Change 1 2	Package	AB	C D	E	F gr
093 0130 599 02	MP 93-130 NERO	52,00	+ 60% -	250	6.5 4 7	.9 1.5	1.5	6

Colour	Colour num	ber					
black	599 (XXX XXXX <b>XXX</b> XX)						
Colour descriptionblackMatchesjet blackFeatured colours reserved. Due to the	ack. Matches: Reas	conably matches RAL colour 9005 es in colour may occur.					
Material		Material nr					
Nylon - 66 PA - 66							
A strong, tough and durable material. selflubricant properties ideal for slide strongst. Therefore always has to acc Nylon is self extinguishing. <b>Features</b>	bearings. Takes in	approx 2 % moisture (a little less th	an nylon-6) and is then at its				
feature	DIN	Resistance to	Valutation				
Relative density gr/cm <sup>3</sup>	1,14	Petrol	А				
Tensile strength MN/m <sup>2</sup>	60	Benzene	A				
Elongation at break %	140	Mineral oils	А				
Tensile modulus MN/m <sup>2</sup>	1500	Vegetable oils	А				
Notched impact strength kJ/m <sup>2</sup>	17	Weak alkalis	А				
Ball indentation MN/m <sup>2</sup>	100	Strong alkalis	В				
Application temperature max °C	120	Weak acids	В				
√olume resistivity cm	10^15	Strong acids	С				
Dissapation factor tan. 10 <sup>3</sup> Hz	0,15	A = good					
Dielectric strength MV/m	30	$\mathbf{B} = doubtful$					
Flammability UL94 > 1,6 mm	V2	<b>C</b> = poor					
	0.0						
Coefficient of friction (on steel)	0,3						

Technical informations are indicative and can be updated. Copyright Gandini Fasteners S.r.I. All rights reserved. No part of this web site may be reproduced in any form without express permission.

GANDINI FASTENERS SRL viale Pier Paolo Pasolini, 83 - 20099 Sesto S.Giovanni Milano Italy Tel. +39 02 241 047 250 Fax +39 02 241 047 74

Production and distribution of fasteners, fixing elements and mechanical parts machining

**GANDINI FASTENERS SRL** Sesto San Giovanni Mi - Italy **Sales department** 250@gandini.it tel +39 02 241 047 250

Administration 350@gandini.it tel +39 02 241 047 350