

TECHNICAL PLASTIC AND METAL PARTS

							Rokut r 093	;
Code	Description	Price euro/1000	% Price Change 1 2	Package	A B	С	D	E F gr
093 0150 599 02	MP 93-150 NERO	76,00	+ 60% -	250	10 6	10.5	2.2	28

Colour	Colour num	ber			
black	599 (XXX)	XXXX XXX XX)			
Colour descriptionblackMatchesjet blackFeatured colours reserved. Due to the	ack. Matches: Reas	conably matches RAL colour 9005 es in colour may occur.			
Material		Material nr			
Nylon - 66 PA - 66		02 (XXX XXXX XXX XXX XX)			
A strong, tough and durable material. selflubricant properties ideal for slide strongst. Therefore always has to acc Nylon is self extinguishing. Features	bearings. Takes in	approx 2 % moisture (a little less the	an nylon-6) and is then at its		
feature	DIN	Resistance to	Valutation		
Relative density gr/cm ³	1,14	Petrol	A		
Tensile strength MN/m ²	60	Benzene	A		
Elongation at break %	140	Mineral oils	A		
Tensile modulus MN/m ²	1500	Vegetable oils	А		
Notched impact strength kJ/m ²	17	Weak alkalis	А		
Ball indentation MN/m ²	100	Strong alkalis	В		
Application temperature max °C	120	Weak acids	В		
Volume resistivity cm	10^15	Strong acids	С		
Dissapation factor tan. 10 ³ Hz	0,15	A = good			
Dielectric strength MV/m	30	B = doubtful			
	1/0	C = poor			
-lammability UL94 > 1,6 mm	V2	e = peer			
Flammability UL94 > 1,6 mm Coefficient of friction (on steel)	V2 0,3				

Technical informations are indicative and can be updated. Copyright Gandini Fasteners S.r.I. All rights reserved. No part of this web site may be reproduced in any form without express permission.

GANDINI FASTENERS SRL viale Pier Paolo Pasolini, 83 - 20099 Sesto S.Giovanni Milano Italy Tel. +39 02 241 047 250 Fax +39 02 241 047 74

Production and distribution of fasteners, fixing elements and mechanical parts machining

GANDINI FASTENERS SRL Sesto San Giovanni Mi - Italy **Sales department** 250@gandini.it tel +39 02 241 047 250

Administration 350@gandini.it tel +39 02 241 047 350