

TECHNICAL PLASTIC AND METAL PARTS

						R	okut riv 093	vet
Code	Description	Price euro/1000	% Price Change 1 2	Package	A B	C D	E	F gr
093 0140 599 02	MP 93-140 NERO	63,00	+ 60% -	250	8.5 5 9	9.2 1.8	3 1.5	7

Colour	Colour num	har				
black	599 (XXX XXXX XXX XX)					
Colour descriptionblackMatchesjet blackFeatured colours reserved. Due to the	ack. Matches: Reas	conably matches RAL colour 9005 es in colour may occur.				
Material		Material nr				
Nylon - 66 PA - 66		02 (XXX XXXX XXX XX)	02 (XXX XXXX XXX XX)			
A strong, tough and durable material. selflubricant properties ideal for slide strongst. Therefore always has to acc Nylon is self extinguishing. Features	bearings. Takes in	approx 2 % moisture (a little less th	an nylon-6) and is then at its			
feature	DIN	Resistance to	Valutation			
	2					
Relative density gr/cm ³ Tensile strength MN/m ²	1,14 60	Petrol Benzene	A			
Elongation at break %	140	Mineral oils	A			
Tensile modulus MN/m ²	140	Vegetable oils	A			
Notched impact strength kJ/m ²	1300	Weak alkalis	A			
Ball indentation MN/m ²	100	Strong alkalis	В			
Application temperature max °C	120	Weak acids	B			
Volume resistivity cm	10^15	Strong acids	С			
Dissapation factor tan. 10 ³ Hz	0,15	A = good				
Dielectric strength MV/m	30	B = doubtful				
Flammability UL94 > 1,6 mm	V2	C = poor				
Coefficient of friction (on steel)	0,3					

Technical informations are indicative and can be updated. Copyright Gandini Fasteners S.r.I. All rights reserved. No part of this web site may be reproduced in any form without express permission.

GANDINI FASTENERS SRL viale Pier Paolo Pasolini, 83 - 20099 Sesto S.Giovanni Milano Italy Tel. +39 02 241 047 250 Fax +39 02 241 047 74

Production and distribution of fasteners, fixing elements and mechanical parts machining

GANDINI FASTENERS SRL Sesto San Giovanni Mi - Italy **Sales department** 250@gandini.it tel +39 02 241 047 250

Administration 350@gandini.it tel +39 02 241 047 350