

TECHNICAL PLASTIC AND METAL PARTS

									Driv	e fa: 09		÷r
Code	Description	Price euro/1000	% Price C 1	Change 2	Package	A	В	С	D	Е	F	gr
091 0001 599 02	MP 91-01 NERO	118,00	+ 60%	-	500	2.4	5.8	3.5	7.6	13	1.1	

Colour	Colour num	ber								
black	599 (XXX)	XXXX XXX XX)								
Colour descriptionblackMatchesjet blackFeatured colours reserved. Due to the	ck. Matches: Reas	onably matches RAL colour 9005 es in colour may occur.								
Material		Material nr								
Nylon - 66 PA - 66		02 (XXX XXXX XXX XX)								
A strong, tough and durable material. Suitable for connecting elements and other technical components. Owing to selflubricant properties ideal for slide bearings. Takes in approx 2 % moisture (a little less than nylon-6) and is then at its strongst. Therefore always has to acclimatize for a few days after injection moulding. Operational temperature up to 120°C. Nylon is self extinguishing.										
feature	DIN	Resistance to	Valutation							
Relative density gr/cm ³	1,14	Petrol	A							
Tensile strength MN/m ²	60	Benzene	А							
Elongation at break %	140	Mineral oils	А							
Tensile modulus MN/m ²	1500	Vegetable oils	А							
Notched impact strength kJ/m ²	17	Weak alkalis	А							
Ball indentation MN/m ²	100	Strong alkalis	В							
	120	Weak acids	В							
Application temperature max °C	120									
	10^15	Strong acids	С							
/olume resistivity cm			C							
Volume resistivity cm Dissapation factor tan. 10 ³ Hz	10^15	Strong acids A = good B = doubtful	C							
Volume resistivity cm Dissapation factor tan. 10 ³ Hz Dielectric strength MV/m	10^15 0,15	Strong acids A = good	C							
Application temperature max °C Volume resistivity cm Dissapation factor tan. 10 ³ Hz Dielectric strength MV/m Flammability UL94 > 1,6 mm Coefficient of friction (on steel)	10^15 0,15 30	Strong acids A = good B = doubtful	C							

Technical informations are indicative and can be updated. Copyright Gandini Fasteners S.r.I. All rights reserved. No part of this web site may be reproduced in any form without express permission.

GANDINI FASTENERS SRL viale Pier Paolo Pasolini, 83 - 20099 Sesto S.Giovanni Milano Italy Tel. +39 02 241 047 250 Fax +39 02 241 047 74

Production and distribution of fasteners, fixing elements and mechanical parts machining

GANDINI FASTENERS SRL Sesto San Giovanni Mi - Italy **Sales department** 250@gandini.it tel +39 02 241 047 250

Administration 350@gandini.it tel +39 02 241 047 350