

С

TECHNICAL PLASTIC AND METAL PARTS

ECHNICAL PLASTIC	AND WETAL PAR	(13				
						Adjustable laminea plug group 063
Code	Description	Price euro/1000	e e e e e e e e e e e e e e e e e e e	Package	A B	C DE F g
063 0555 114 01	MP 63-555 NERO	683,00	1 2 + 60% -	100	25 21.	5 M8 F2
Colour		Colour number				
black		14 (XXX XXXX X				
Material			Material nr			
Nylon - 6 PA - 6		(01 (XXX XXXX XXX X	(X)		
General informations: A strong, tough and dura lubricant properties idea Always has to acclimatiz Features	I for slide bearings. T	akes in approx 3% erational temperate	moisture at room temp	erature and	is then a	t its strongest.
eature	D	DIN I	Resistance to		١	/alutation
Relative density gr/cm ³	1	,14 I	Petrol		ŀ	4
Fensile strength MN/m ²	5	5 I	Benzene		A	Ą
Elongation at break %	2	50 I	Vineral oils		ŀ	Ą
Γensile modulus MN/m ²	9	50	Vegetable oils		A	4
Notched impact strength	kJ/m ² 3	5	Weak alkalis		A	Ą
Ball indentation MN/m ²	8	2	Strong alkalis		E	3
Application temperature	max °C 1	20	Weak acids		E	3
		a =	• / • •			~

Technical informations are indicative and can be updated.

Volume resistivity cm

Dielectric strength MV/m

Dissapation factor tan. 10³ Hz

Flammability UL94 > 1,6 mm

Coefficient of friction (on steel)

All data are indicative

Copyright Gandini Fasteners S.r.I. All rights reserved. No part of this web site may be reproduced in any form without express permission.

Strong acids

A = good B = doubtful

C = poor

GANDINI FASTENERS SRL viale Pier Paolo Pasolini, 83 - 20099 Sesto S.Giovanni Milano Italy Tel. +39 02 241 047 250 Fax +39 02 241 047 74

10^15

0,2

35

V2

0,3

Production and distribution of fasteners, fixing elements and mechanical parts machining

GANDINI FASTENERS SRL Sesto San Giovanni Mi - Italy **Sales department** 250@gandini.it tel +39 02 241 047 250

Administration 350@gandini.it tel +39 02 241 047 350