

SMALLEY® WAVE SPRINGS

Acciaio al Carbonio per Molle
SAE 1070-90

surface finishes
Oliatura

Esempio di designazione: C025-L1

C = Base ondulata
tipi da C 025-L1 a C 200-H10



d1=diametro foro guida
d4=diametro albero guida
S=spessore
H=altezza libera
H1=altezza lavoro

C - serie in pollici
base ondulata



description	Price Euro x100	% Price Change		Package
		1	2	
C087-M5	140,00	+ 20%	-	100

WAVE			
description C087-M5		s	inch. 0,012 mm 0,30
d1 - bore diameter	inch. 0,875 mm 22,23	b	inch. 0,094 mm 2,39
d4 - shaft diameter	inch. 0,600 mm 15,24	spring rate (Theoretical value)	Lb/inch 66 N/mm 12
Load	Lb in H1 18,00 N in H1 80,10		
H1 work height	inch. 0,296 mm 7,52		
H free height	inch. 0,583 mm 14,81		
turns nr	7		
wave nr	3,5		
Weight Kg/1000	2,49		

Technical informations are indicative and can be updated.

Copyright Gandini Fasteners S.r.l. All rights reserved. No part of this web site may be reproduced in any form without express permission.

GANDINI FASTENERS SRL viale Pier Paolo Pasolini, 83 - 20099 Sesto S.Giovanni Milano Italy
Tel. +39 02 241 047 250 Fax +39 02 241 047 74

Production and distribution
of fasteners, fixing elements
and mechanical parts
machining

GANDINI FASTENERS SRL
viale Pier Paolo Pasolini, 83
Sesto San Giovanni Mi - Italy

Sales department
250@gandini.it
tel +39 02 241 047 250

Administration
350@gandini.it
tel +39 02 241 047 350