

## CYLINDRICAL, TAPER AND GROOVED PINS

### MATERIAL:

100 Cr 6 (1.3505)  
Hardness 58 ÷ 62 HRC  
Resistance > 600 N/mm<sup>2</sup>

### Ground



PARALLEL PINS  
**DIN 6325**  
hardened (m6)

ISO 8734  
UNI 6364 A



| L     | tolerance | d (m6) | description        | Price<br>Euro /100 | % Price Change<br>1 2 | Package | a ≈ | c   |
|-------|-----------|--------|--------------------|--------------------|-----------------------|---------|-----|-----|
| 10.00 | ± 0,25    | 2.0    | <b>2 X 10 (m6)</b> | <b>8,60</b>        | - -                   | 500     | 0,3 | 0,8 |

Technical informations are indicative and can be updated.

Copyright Gandini Fasteners S.r.l. All rights reserved. No part of this web site may be reproduced in any form without express permission.

**GANDINI FASTENERS SRL** viale Pier Paolo Pasolini, 83 - 20099 Sesto S. Giovanni Milano Italy

Tel. +39 02 241 047 250 Fax +39 02 241 047 74

Production and distribution  
of fasteners, fixing elements  
and mechanical parts  
machining

**GANDINI FASTENERS SRL**  
viale Pier Paolo Pasolini, 83  
Sesto San Giovanni Mi - Italy

**Sales department**  
250@gandini.it  
tel +39 02 241 047 250

**Administration**  
350@gandini.it  
tel +39 02 241 047 350