


CYLINDRICAL, TAPER AND GROOVED PINS

MATERIAL:

100 Cr 6 (1.3505)
Hardness 58 ÷ 62 HRC
Resistance > 600 N/mm²

Ground



Execution with breather air depending on manufacturer's choice

CYLINDRICAL PINS
DIN 7979 D
hardened (m6)
with internally threaded

ISO 8735
UNI 6364 B



L	tolerance	d ₁ (m6)	description	Price Euro /100	% Price Change 1	2	Package	a	c	d ₂	t ₁
60.00	± 0,75	6.0	6 X 60 (m6)	110,00	-	-	50	0,8	2,1	M4	6

Technical informations are indicative and can be updated.

Copyright Gandini Fasteners S.r.l. All rights reserved. No part of this web site may be reproduced in any form without express permission.

GANDINI FASTENERS SRL viale Pier Paolo Pasolini, 83 - 20099 Sesto S.Giovanni Milano Italy
Tel. +39 02 241 047 250 Fax +39 02 241 047 74

Production and distribution
of fasteners, fixing elements
and mechanical parts
machining

GANDINI FASTENERS SRL
viale Pier Paolo Pasolini, 83
Sesto San Giovanni Mi - Italy

Sales department
250@gandini.it
tel +39 02 241 047 250

Administration
350@gandini.it
tel +39 02 241 047 350